

MASTER FloorSTICKER

Textured Floor Graphic Polyester Film



Certified for HP Latex Inks

CERTIFIED













Applications

- Indoor floor graphic displays
- Supermarkets, shopping malls, convention centres, airports
- All smooth hard floors e.g. concrete & tiling
- Low Pile Carpet tiles

Benefits

- Unique sharkskin coating absorbs the ink & dries tough
- Eliminates the need to laminate
- Sharkskin structure gives great color gamut and high grip; R10 certified
- Easy to apply & easy to remove, does not tear into small pieces when removing
- No shrinkage no risk of a rim of dirty adhesive forming around the print
- Ultra-tough polyester base, resists tearing, resists pallet trucks & stiletto heels

Thickness:

170 224 6.7 mil gsm

Available widths:

1372 1524 54" 60"

Adhesion:

AFTER 24H 16 N /25mm

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "gas-out" after printing. This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH

