



## Master 15ATO

Gloss clear overlay polyester film



### Thickness & Weight

127µm – 156 g/m<sup>2</sup>

### Roll Widths & Lengths

914mm-30m

### Recommended conditions

Printroom 15°C - 30°C, 30% - 65% RH

For use -40°C - 80°C, 10% - 90% RH

For storage 10°C - 20°C, 20% - 50% RH

Shelf Life 24 months after delivery  
(under recommended  
storage conditions)

### Compatibility

**Aqueous Dye**



**Aqueous Pigment**



### Characteristics

- Clear glossy film
- Removable two edge striped for printer recognition
- Packaged with interleaving

### Applications

- Colour and monochrome overlays for maps and plan schematics
- Ideal full colour reproductions

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "Gas-out" after printing. This can be achieved by leaving the prints face up, ideally for 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

APPFACORY - Inspired by print applications

+32 9 331 53 88

[info@appfactorydigital.com](mailto:info@appfactorydigital.com)

[www.appfactorydigital.com](http://www.appfactorydigital.com)