



## Master 23AGPF

Gloss white permanent self-adhesive film



Thickness &Weight	Compatibility		
	Aqueous Dye	Aqueous Pigrment	
50µm – 235 g/m2	$\checkmark\checkmark\checkmark$	$\checkmark$	
Roll Widths & Lengths	Characteristics		
914mm-20m			
Recommended conditions	<ul> <li>Rapid drying and smear resistant</li> <li>Standard acrylic adhesive, initially repositionable increasing to permanent</li> </ul>		
Printroom 15°C - 30°C, 30% - 65% RH			
For use -40°C - 80°C, 10% - 90% RH			
For storage 10°C - 20°C, 20% - 50% RH			
Shelf Life 24 months after delivery (under recommended storage conditions)			
	Applications		

- Self-adhesive displays

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "Gas-out" after printing. This can be achieved by leaving the prints face up, ideally for 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

APPFACTORY - Inspired by print applications +3293315388 <u>info@appfactorydigital.com</u> <u>www.appfactorydigital.com</u>