



Master 23TLB

Textured Lightblock Roll-Up Polyester Film



Thickness & Weight

230 μ m - 305g/m²

Roll Widths & Lengths

914mm-30m
1270mm-30m
1524mm-30m

Recommended conditions

Printroom 15°C - 30°C, 30% - 65% RH

For use -40°C - 80°C, 10% - 90% RH

For storage 10°C - 20°C, 20% - 50% RH

Shelf Life 24 months after delivery
(under recommended
storage conditions)

Compatibility

Mid Solvent

✓✓✓

Eco Solvent

✓✓✓

Latex

✓✓✓

UV

✓✓✓

Characteristics

- Premium roll-up material - grey back, 98% opacity
- Textured, anti-reflective bright-white front surface
- Scratch and water resistant (No need for lamination)
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness
- PVC Free

Applications

- Roll-up displays

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "Gas-out" after printing. This can be achieved by leaving the prints face up, ideally for 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

APPFACORY - Inspired by print applications

+32 9 331 53 88

info@appfactorydigital.com

www.appfactorydigital.com