



## Master Optimum R3

Textured Lightblock Roll-Up Film PET + PVC



### Thickness & Weight

310 µm – 415 g/m<sup>2</sup>

### Roll Widths & Lengths

914mm-30m  
1067mm-30m  
1270mm-30m  
1372mm-30m  
1542mm-30m

### Recommended conditions

Printroom	15°C - 30°C, 30% - 65% RH
For use	-40°C - 80°C, 10% - 90% RH
For storage	10°C - 20°C, 20% - 50% RH
Shelf Life	24 months after delivery (under recommended storage conditions)

### Compatibility

Mid Solvent

✓✓✓

Eco Solvent

✓✓✓

Latex

✓✓✓

UV

✓✓✓

### Characteristics

- Grey back 98% opacity
- PVC frontside for easy printing + PET backside for optimal stay-flat
- Lightly textured surface
- Suitable for indoor and outdoor use
- Scratch resistant, no need for lamination
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness

### Applications

- Roller banner displays

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "Gas-out" after printing. This can be achieved by leaving the prints face up, ideally for 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

APPFACORY - Inspired by print applications

+329 331 53 88

[info@appfactorydigital.com](mailto:info@appfactorydigital.com)

[www.appfactorydigital.com](http://www.appfactorydigital.com)