



## Master 38TLB

### Textured Lightblock Pop-Up Polyester Film



#### Thickness & Weight

385µm - 540g/m<sup>2</sup>

#### Roll Widths & Lengths

914mm-20m  
914mm-30m  
1270mm-20m

#### Recommended conditions

Printroom 15°C - 30°C, 30% - 65% RH

For use -40°C - 80°C, 10% - 90% RH

For storage 10°C - 20°C, 20% - 50% RH

Shelf Life 24 months after delivery  
(under recommended storage conditions)

#### Compatibility

Mid Solvent



Eco Solvent



Latex



UV



#### Characteristics

- Premium Pop-up material - grey back, 98% opacity
- Textured, anti-reflective bright-white front surface
- Scratch and water resistant (No need for lamination)
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness
- PVC Free

#### Applications

- Pop-up displays

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "Gas-out" after printing. This can be achieved by leaving the prints face up, ideally for 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

APPFACORY - Inspired by print applications

+329 331 53 88

[info@appfactorydigital.com](mailto:info@appfactorydigital.com)

[www.appfactorydigital.com](http://www.appfactorydigital.com)