



Master Floor Sticker

Self-Adhesive Floor Polyester Film



Thickness & Weight

170µm

Roll Widths & Lengths

1372mm-25m
1524mm-25m

Recommended conditions

Printroom	15°C - 30°C, 30% - 65% RH
For use	-40°C - 80°C, 10% - 90% RH
For storage	10°C - 20°C, 20% - 50% RH
Shelf Life	24 months after delivery (under recommended storage conditions)

Compatibility

Mid Solvent



Eco Solvent



Latex



UV



Characteristics

- Unique coating absorbs the ink & dries tough
- No need to laminate
- Structure gives great color gamut and high grip; R10 certified
- Easy to apply & easy to remove, does not tear into small pieces when removing
- No shrinkage – no risk of a rim of dirty adhesive forming around the print
- Ultra-tough polyester base, resists tearing, resists pallet trucks & stiletto heels
- Applicable to all smooth, hard floors e.g. concrete & tiling

Applications

- Indoor floor graphic displays
- Supermarkets, shopping malls, convention centres, airports

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "Gas-out" after printing. This can be achieved by leaving the prints face up, ideally for 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.