



EXPERT 22FS – 220g/m² matt white textured Floor Sticker with R10 anti-slip certification

Expert 22FS is a textured white R10 slip resistant dry toner print receptive PET film, with an optimised pressure sensitive adhesive for floor graphic applications. The construction is optimized for dry toner print applications.



Physical characteristics

Property	Typical Value	Unit	Test Method
Total Thickness	300 +/- 6	μ	ISO 534
Total Weight	346 +/- 6	gsm	ISO 536
Face Film Thickness (no adhesive)	153 +/- 4	μ	ISO 534
Face Film Weight	195 +/- 5	Gsm	ISO 536
Liner Thickness	120 +/- 3	μ	ISO 534
Liner Weight	130 +/- 3	Gsm	ISO 536
Adhesive Thickness	27 +/- 5	μ	ISO 534
Adhesive Peel on Stainless Steel	8.5 +/- 1.5	N/25mm	FINAT 1 (Modified) 25mm strip/30 min dwell
Adhesive Application Temperature	+ 5 to + 50	° C	Internal method
Adhesive Service Temperature	-40 to +180	° C	Internal method

Availability Sheets/Pack

SRA3	50/250
------	--------

Recommended conditions

For use	10° C – 30° C, 40% - 55% RH
For storage	10° C – 20° C, 20% - 55% RH
Shelf life	24 months after delivery (under recommended storage conditions)

Compatibility

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and color small-volume, mid-volume & production machines. On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Applications and characteristics

- ✓ Unique sharkskin coating, toner bonding & scratch resistant
- ✓ No lamination required
- ✓ R10 anti-slip certified
- ✓ Durable surface, resists scuffing & stiletto heels
- ✓ Perfect for floor graphic applications such as floor signage & "walk-on" advertisements in retail chains
- ✓ Easy to apply & easy to remove, no glue residue

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.