



## EXPERT 26H – 260g/m<sup>2</sup> Horizontal Pre-Fold Matt Film

Expert 26H is a 260gsm 2-side matt aqueous coated polyester film with a horizontal pre-fold, optimised for Production & Digital Press print applications.



### Physical characteristics

Property	Typical Value	Unit	Test Method
Weight	261 +/- 6	g /m2	Internal Method
Thickness	193 +/- 5	μ	Electronic Micrometer
Opacity	>98	%	TAPPI T519
CIE Whiteness	>140	CIE WI	ASTM E313 DCI Spectraflash ( D65, 10° observer, UV incl.)
Melting Point	250	° C	ASTM E794-85
Usage Temperature	-40 - +120	° C	Internal method

### Availability

### Sheets/Pack

A4 100/500

### Recommended conditions

For use 10°C - 30°C, 40% - 55% RH

For storage 10°C - 20°C, 20% - 55% RH

Shelf Life 24 months after delivery (under recommended storage conditions)

### Compatibility

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines. On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material. The printable surface is also suitable for screen print, offset litho (using only fully oxidising inks).

### Applications and characteristics:

It has a smooth matt surface giving a strong dense image with excellent print adhesion and can be printed on both sides where equipment allows.

- ✓ Water resistant, wipeable and punchable.
- ✓ Ideal for instant landscape style menus.
- ✓ Replaces the need for paper to be printed and then encapsulated.

**NOTICE** The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.